

# **DWS-NO3 / DWS-TAN**

### **Point-of-Entry Treatment Solutions for Nitrates or Tannins**

DWS-NO3 (Whole Home Iron/Hardness/Nitrate Removal)

DWS-TAN (Whole Home Iron/Hardness/Tannin Removal)



## ESS1152

#### **ECOWATER 1100 SERIES** WATER SOFTENER



#### **SPECIFICATIONS**

	ESS1152R32
Supply Water Pressure Limits (psi)1	20-125
Supply Water Temperature Limits ("F/C")	40-100/4-38
Service Flow Rate (gpm) <sup>2</sup>	9
Approximate Water Used Each Regeneration (gal.) <sup>2</sup>	41
Salt Storage Capacity (lbs.)	300

Electrical Requirement, 120V, 50/60Hz, (24V DC, 500 mA, power supply included)

<sup>1</sup>Maximum pressure for Canadian use is 7.0 kg/cm<sup>2</sup>. <sup>2</sup>Not to exceed 15 psi pressure loss <sup>3</sup>When operated at 35 psi water pressure

#### WARRANTY

- . For the lifetime of the original owner, the mineral tank will not rust, corrode, leak, burst, or in any other manner fail to perform its proper function.
- . For a period of ten years, the salt tank will be free of defects in materials and workmanship and will perform its proper function.
- For a period of three years, the valve body, electronic faceplate and all other parts will be free of defects in materials and workmanship and will perform their normal functions.





**√**\_}

 Mixed Sources FSC www.hcsg.com/stars.com/



NSF





ecowater.com